

Filtration Product Guide

C A R T R I D G E S H O U S I N G S B A G S



**ROSEDALE
PRODUCTS INC.**



Filter Housings.

**Models 4, 6, 8****LCO & Coolant Filter****4 & 8 Indicating****8-125 Bag Filter**

APPLICATION	General Liquid Straining & Filtration			Low Cost High Duty Straining & Filtration		Filter & Strainer, Visual Indicator	Simple Filtration & Straining with Easy Access
HOUSING SIZE	4	6	8	LCO4 LCO6 LCO8		4 & 8	8-125
PIPE SIZE (INCHES)	3/4 to 2 NPT or ANSI	3/4 to 2 NPT or ANSI	3/4 to 3 NPT 3/4 to 6 ANSI	3/4 to 2 NPT (LCO4)	1-1/2 & 2 NPT (LCO6 and 8)	3/4 to 1 NPT 3/4 to 2 ANSI	2 NPT
OUTLET STYLE	Side In/Out, Bottom Out			Side/Bottom Unistyle		Side In/Out, Bottom Out	Side/Bottom Unistyle
PRESSURE RATING	150 to 500		150 to 300	125 & 200		150 200 300	125

AVAILABLE BAGS



Standard



Polypro Top



Beta Rated



Pleated



Graded Density



X-tend



Giardia

**Model 82 Housing****Multi-Bag Housing****Duplex/Auto Duplex****Auto Backwash**

Dual Capacity Liquid Filtration & Straining	High Flow & High Capacity Liquid Filtration	Continuous Operation Liquid Filtration	Continuous Filtration with Automatic Backwashing
82	16, 18, 22, 24, 30, 36, 42, 48	4, 6, 8, 16, 18, 22, 24, 30, 36, 42, 48, 82	8
2 to 6 NPT	2 to 12	1 to 12 ANSI	2 to 12 ANSI
Side In, Bottom Out	Bottom In/Out (std) Side In/Out or Side In/Out Same Side (SLP, HLP, QII)	Side In, Side Out	Bottom In, Side Out
150 & 300	150	150	150

AVAILABLE CARTRIDGES

Disposable



Platinum 500



OE



Basket Converter

See additional Bag and
Cartridge options on
pages 10-12.



Filter Housings.

**Aluminum Housing****Multiplex****Manual Backwash****Sanitary Filter**

	Aluminum Housing	Multiplex	Manual Backwash	Sanitary Filter
APPLICATION	Economical, Heavy Duty Housings	Continuous Liquid Filtration & Straining	Liquid Filter with Manual Backwash	USDA/3A Dairy Standards
HOUSING SIZE	4, 6, 8	8	8	4, 8
PIPE SIZE (INCHES)	3/4 to 3 NPT	3 to 8 ANSI	2 to 4 NPT or ANSI	1 to 1-1/2 Tri-Clamp Connections
OUTLET STYLE	Side High 180, Side Low 180, Same Side High, Same Side Low Bottom	Side In, Bottom Out on Manifolds	Side Out, Bottom In	Side In, Bottom Out
PRESSURE RATING	125 150 300	150	150	200

AVAILABLE BAGS



Standard



Polypro Top



Beta Rated



Pleated



Graded Density



X-tend



Giardia

**NCO Filter****Model OT****Giardia Filter****Portable Filtration**

NCO Filter	Model OT	Giardia Filter	Portable Filtration
Low Cost Liquid Filtration	Over the Top Liquid Filtration	LT2 Compliant Removal of Giardia & Other Cysts From Potable Water	Portable Liquid Filtration, One Housing Services Multiple Locations
8	8	8	8
1-1/2 to 2 NPT	2 NPT or ANSI	2 NPT or ANSI	1 NPT
Side In/Out Bottom Out	Over the Top In, Bottom Out	Side In, Bottom Out	Side In, Bottom Out
150	150	150	125

AVAILABLE CARTRIDGES

Disposable



Platinum 500



OE



Basket Converter

See additional Bag and
Cartridge options on
pages 10-12.

Filter Housings.



Coolant Filter Cart



Convertible



Polypro Model 8



Cartridge Filter

	Coolant Filter Cart	Convertible	Polypro Model 8	Cartridge Filter
APPLICATION	Portable Coolant Filtering, One Housing Services Multiple Tanks	Single Housing, Uses Either Bag or Cartridge	Industrial, Potable, Ultra Pure & Deionized Applications	Cartridge Filtration- 1 to 208 Cartridges
HOUSING SIZE	8	6, 8	8	4, 6, 8, 12, 16, 18, 22, 24, 30, 36, 42, 48
PIPE SIZE (INCHES)	1 NPT	3/4 to 3 NPT or ANSI	2 NPT	3/4 to 3 NPT 3/4 to 12 ANSI
OUTLET STYLE	Side In, Bottom Out	Side In, Bottom Out	Side/Bottom Unistyle	Side In, Bottom Out
PRESSURE RATING	125	150 & 300	100	150 & 300
AVAILABLE MEDIA	Holds all media from pages 2-3	 Membrane  Wound SS Holds all media from pages 2-3 plus the media above	 Platinum 700 Holds all media from pages 2-3 plus the media above	 Membrane  Wound SS


Platinum 700

High Flow System

Model 7180

Heat Transfer Filter

High Contaminant Load Liquid Filtration	High Flow Filtration Systems	Hydraulic Lube-Oil Filter	300°F to 700°F
8	8, 18, 24, 30, 36, 42, 48	8	8, 18, 24
2 NPT or ANSI	2 to 14 ANSI	1, 1-1/2, or 2 NPT	1 to 6 ANSI
Side In, Bottom Out	Side In, Side Out	Side In, Side Out	Side Bottom, Side Side
100 125 150	150 & 300	150	85
 Platinum 700	 High Flow Element	 718 or 736 Cartridge	 Stainless Steel Wire Cloth-Wedge Wire or Glass Fiber-Wound Elements

Filter Housings.



Coalescer Filter




HSS/HSS750



Sorbent Containment



Separator

	Coalescer Filter	HSS/HSS750	Sorbent Containment	Separator
APPLICATION	Liquid Coalescence of Gas Streams	Single Cartridge Liquid Housing	General	Solid/Liquid Separation
HOUSING SIZE	—	Custom	4, 8	—
PIPE SIZE (INCHES)	1 to 8 NPT or ANSI	1 NPT (HSS) 3/4 NPT (HSS750)	3/4 to 6 NPT or ANSI	3/8 to 2-1/2 NPT 3 to 10 ANSI
OUTLET STYLE	Side In, Side Out	Top In, Top Out	Side In, Bottom Out	Side In, Top Out
PRESSURE RATING	75 to 3000	150 (HSS) 750 (HSS750)	150 to 300	150
AVAILABLE MEDIA	 Coalescer Cartridge	 M101/M102 Wound	 Sorbent	None Required



Vibrating Filter



RBS Housing



Platinum 900/2040



High Pressure Filter

Vibrating Filter	RBS Housing	Platinum 900/2040	High Pressure Filter
Viscous Liquid Filtration	Fabricated Basket Strainer	High Capacity, High Contaminant-Load Liquid Filtration	Oil & Gas Applications
4	Custom	18, 30, 36, 42, 48	8
3/4 to 2 NPT 1 to 2 ANSI	2 to 24 ANSI	2 to 10 ANSI	1 to 6 ANSI
Side In, Bottom Out	Top In, Top Out	Bottom In, Bottom Out	Side Bottom, Side Side
300	150 (HSS) 750 (HSS750)	150	740 & 1440
 SS	 Mesh Lined & Perforated Baskets	 Platinum 900/2040 (Single Large Element)	Holds all media from pages 2-3



Filter Cartridges & Strainer Baskets.

							
	Disposable Pleated Cartridges	Standard Platinum 500	Series OE	Basket Converter	Sorbent Containment	Perforated & Perforated Mesh Lining	
APPLICATION	Disposable Pleated Cartridges	High Capacity Absolute Efficiency	Oil/Water Separation	General	Purification	General	
DESCRIPTION	Low Cost High Capacity Filtration	Beta 5000 Rated 99.98%	Environmental Applications	Converts Bag Housing to Cartridge	Organic Removal of Odors & Contaminants	Cleanable Strainer	
FITS HOUSINGS							
	4, 6, 8	LCO	Indicating	8-125	82		
							
	Multi-Bag	Duplex	Polypro	Multiplex	Manual Backwash		
							
	Sanitary	NCO	OT	Giardia	Portable		
							
	Coolant	Convertible					



Standard
Wound



Standard
Stainless
Steel



Absolute
Pleated



GSC, FSC, PS,
ES, WS



Standard
Platinum 700



Standard
Platinum
900/2040



High Flow
Element

General	General	High Capacity Efficiency	Industrial Filter Membrane Cartridges	High Capacity Absolute Efficiency		
All Purpose	Rated 5-800 Microns	Rated to 0.5 Microns	General Service Food, Beverage, Pharmaceutical, Electronics, Water Service	Dirt capacity exceeds 20 lbs	Dirt capacity exceeds 100 lbs - 900 250 lbs - 2040	Up to 31 elements at 400 gpm per element
 Cartridge Filter				 Platinum 700	 Platinum 900/2040	 High Flow System



Bags.



	Standard Filter Bags	Polypropylene Filter Bags	High Efficiency Filter Bags	
APPLICATION	General	General	General	High Capacity Absolute Efficiency
MODEL SERIES / DESCRIPTION	Rosedale Top / Economy	Polypropylene Top / 1-110 Microns	 Beta Rated / 1-12 Microns	 Pleated Bag Sized / 1-110 Microns
	Standard Felt / 1-100 Microns			 X-Tend / 1-110 Microns
	Standard Mesh / 50-800 Microns		 Graded Density / 1-19 Microns	
	Standard OA / Oil Adsorbent		 Giardia Removal / 3 Microns	
	Standard Teflon® / High Temp			
	Standard Nomex / High Temp			

FITS HOUSINGS



4, 6, 8



LCO



Indicating



8-125



82



Multi-Bag



Duplex



Auto Backwash



Multiplex



Sanitary



NCO



OT



Portable



Coolant



Convertible



Polypro



Platinum
900/2040



**ROSEDALE
PRODUCTS INC.**



QUALITY
SYSTEM
REGISTERED TO
ISO 9001

DISTRIBUTOR TERRITORIES AVAILABLE WORLDWIDE

3730 West Liberty Road - Ann Arbor, MI 48103

Phone: 734.665.8201 • Fax: 734.665.2214

Email: Filters@RosedaleProducts.com

RosedaleProducts.com • GiardiaFilters.com

©2015 Rosedale Products Inc. • Catalog CL-118 7.5M • 09/2015