



COST EFFECTIVE FILTRATION

## Filter: Bag Filters for Fine Sanitary Filtration.

Rosedale sanitary service filters conform to USDA/3A dairy standards with housings of polished 316 stainless steel and have quick-release clamp-type covers. Outlets and inlets have sanitary flange connections. All internal surfaces can be visually inspected (and easily cleaned in place).

### CONSTRUCTION

Housings are all welded construction with all wetted parts of 316 stainless steel. All welded attachments are 300 series stainless steel. The materials and manufacturing process exceed industry standards for sterile filtration.

### APPLICATIONS

Dairy, beverage, vegetable oils, and other foods and pharmaceuticals. They also make excellent pre-filters upstream of ultra-fine cartridge and membrane filters.

### SPECIFICATIONS

- Material: 316 stainless steel
- Surface Finish: 150 grit (25 RA)
- Inlet/Outlet Connection: 2" sanitary flange
- Vent/Drain: purge valves
- Filter Bag/Cartridge: accepts (1) #1 and #2 trade size filter bag or 500 series filter cartridge
- Operating Pressure: 100 psi (6.8 bar)



Model 8.

PRESSURE RATINGS	MAXIMUM PRESSURE @ 70°	MAXIMUM PRESSURE @ 250°
MODEL 8	100 PSI	50 PSI